

Specifications for the FireGuard® BRAVO Extrication gloves with CROSSTECH® glove inserts: Style 1999

I. Construction:

- a) Design: Glove shall be five-fingered, Montpelier cut, with wing thumb.
- b) Outer Shell: Entire outer glove shall be constructed of poly-spandex. Color: Black.
- c) Moisture Barrier: Separate CROSSTECH® glove insert with new barrier film technology for penetration resistance against blood, body fluids and NFPA common chemicals. Insert must be sized to fit the outer shell.
- d) Cushioned knuckle patch across back of glove.
- e) Leather wear patches on the palm and tips of thumb and index finger.
- f) Rubberized wear patches on tips of other three fingers.
- g) Two-inch, 2-ply wristlet with pull-tab on all gloves.
- h) Elastic snugger on back side of glove.
- i) Available in 6 sizes: XS, S, M, L, XL and 2XL.
- j) Each pair individually packaged with maintenance and inspection instructions plus NFPA Safety Guide.

II. Performance

Certified to NFPA-1999-2008 Edition by S.E.I.

Cat. No. Specify sizes: XS, S, M, L, XL and 2XL

1999 – BRAVO Extrication Glove with CROSSTECH® glove insert

Hansen Fire & Safety

INNOVATIVE PRODUCTS FOR FIRE, EMERGENCY & SAFETY
1395 GRANDVIEW AVE., SUITE 10 • COLUMBUS, OH 43212
PHONE: [800] 369-1800 • FAX: [800] 969-8886